

ød		^	Р	С		Е	_	
O.D	DN	NB	A   B			D	=	F
16	10	3/8"	88	54	130	_	52	
20	15	1/2"	88	54	132	_	52	
25	20	3/4"	_	_	_	_	_	
32	25	1"	_	_	_	_	_	
40	32	11/4"	_	_	_	_	_	
50	40	1½"	_	_	_	_	_	
63	50	2"	_	_	_	_	_	

SWITCH RATING 100 VA @ 40 V MAX

PROTECTION IP65 WITH BOOT **IP00 WITHOUT BOOT** 



CED.	MUCES	חד ו

VALVE SHOWN WITH PROTECTIVE BOOT IN PLACE.

VALVES DO NOT HAVE HOLD DOWN FIXED SCREWS

SWITCH DIAPHRAGM HOUSING ASSEMBLY IS PVC WITH DIAPHRAGM MATERIAL TO MATCH VALVE

ALL DIMENSIONS IN MM UNLESS OTHERWISE

TOLERANCES: ± 0.5 UNLESS STATED

SWITCH ORIENTATION IS SUPPLIED AS SHOWN

UNLESS OPPOSITE IS REQUESTED.

IN THIS CONFIGURATION.

DIMENSION 'C' ± 1.00 MM

DIAPHRAGM.

STATED.

CONGLETON, CHESHIRE, CW12 2AD, ENGLAND

DRAWING No. PS/13/1000 REV 0

O	DRAWN	RB		DATE	04.06.13
REV			REV		
REV			REV		

SUBJECT 1100 SERIES WITH PRESSURE **SENSOR - 316 UNION CONNECTIONS**